



WATTS & VOLT W(FR) PVC INSULATED SINGLE CORE UNSHEATHED INDUSTRIAL (MULTI-STRAND) CABLE : W (FR) FLAME RETARDANT CONFORMING TO IS -694:2010 WITH HIGH QUALITY BARE COPPER CONDUCTOR SUITABLE FOR 1100 VOLTS.

SIZE (Sq. mm.)	No. & SIZE OF WIRE IN MM	CURRENT (AMPS) BUNCHED & ENCLOSED IN CONDUIT OR TRUNKING	RATE PER 90 MTR COIL	STANDARD PACKING FOR 90 MTR	RATE PER 180 MTR COIL	STANDARD PACKING FOR 180 MTR	RATE PER 270 MTR COIL	RATE PER MTR
0.75	10/0.30	7	990	20	1962	10	2943	11.00
1.0	14/0.30	11	1296	20	2574	10	3861	14.40
1.5	22/0.30	14	1962	16	3906	10	5859	21.80
2.5	36/0.30	19	3159	10	6300	5	9450	35.10
4.0	56/0.30	26	4860	6	9702			54.00
6.0	84/0.30	31	7182	4	14346			79.80
SIZE (Sq. mm.)	No. & SIZE OF WIRE IN MM	CURRENT (AMPS) BUNCHED & ENCLOSED IN CONDUIT OR TRUNKING	RATE PER 100 MTR COIL	STANDARD PACKING FOR 100 MTR	RATE PER 200 MTR COIL	STANDARD PACKING FOR 200 MTR		RATE PER MTR
10.0	142/0.30	51	13392	1		1		133.92
16.0	226/0.30	68	20574	1		1		205.74
25.0	354/0.30	86	28822	1		1		288.22
35.0	495/0.30	110	44415	1		1		444.15

WATTS & VOLT W (FRLS) PVC INSULATED SINGLE CORE UNSHEATHED INDUSTRIAL (MULTI-STRAND) CABLE : W(FRLS) FLAME RETARDANT LOW SMOKE CONFORMING TO IS-694:2010 WITH HIGH QUALITY BARE COPPER CONDUCTOR SUITABLE FOR 1100 VOLTS.

SIZE (Sq. mm.)	No. & SIZE OF WIRE IN MM	CURRENT (AMPS) BUNCHED & ENCLOSED IN CONDUIT OR TRUNKING	RATE PER 90 MTR COIL	STANDARD PACKING FOR 90 MTR	RATE PER 180 MTR COIL	STANDARD PACKING FOR 180 MTR	RATE PER 270 MTR COIL	RATE PER MTR
0.75	10/0.30	7	1044	20	2070	10	3105	11.60
1.0	14/0.30	11	1369	20	2720	10	4080	15.21
1.5	22/0.30	14	2070	16	4122	10	6183	23.00
2.5	36/0.30	19	3330	10	6642	5	9963	37.00
4.0	56/0.30	26	5220	6	10422			58.00
6.0	84/0.30	31	7560	4	15102			84.00

NOTE:

- The rates mentioned are not including GST, which shall be charged extra.
- This price list is subject to change without prior notice.
- In accordance to the international practice adapted by the Bureau of Indian Standards the diameter of the conductor displayed above is nominal. The resistance determines by the size of the conductor.
- WATTS & VOLT W (FR) PVC Insulated Industrial Cables are available in 90, 180, and 270 Mtr coils packed in Master as Cartons mentioned above.
- WATTS & VOLT W (FR) PVC Insulated cables are available in five colours : Red, Yellow, Blue, Black & Green.
- WATTS & VOLT W (FRLS) PVC Insulated Industrial Cables are available in 90, 180, and 270 Mtr coils packed in Master as Cartons mentioned above.
- WATTS & VOLT W(FRLS) PVC Insulated cables are available in five colours : Red, Yellow, Blue, Black & Green.

PVC MULTI CORE INDUSTRIAL CABLES

HSN CODE : 8544

WATTS & VOLT FLEXIBLE PVC INSULATED MULTI CORE UNSHEATHED INDUSTRIAL (MULTI-STRAND) CABLE WITH BRIGHT ANNEALED ELECTROLYTIC BARE COPPER CONDUCTOR FOR VOLTAGE UP TO 1100V CONFIRMING TO IS 694:2010.

HSN CODE : 8544

(Rate in Per 100 Mtrs.)

SIZE (Sq. mm.)	COND. CONST. (No./DIA.MM)	2 CORE	3 CORE	4 CORE
0.75	10/0.30	2970	3708	4635
1.0	14/0.30	3870	5130	6480
1.5	22/0.30	5850	7830	9810
2.5	36/0.30	9450	12600	15750
4.0	56/0.30	14580	19440	24300
6.0	84/0.30	21600	28800	

3 CORE FLAT CABLES

SIZE (Sq. mm.)	COND. CONST. (No./DIA.MM)	RATE (Per 100 Mtrs.)
1.5	22/0.30	7740
2.5	36/0.30	12330
4.0	56/0.30	19080
6.0	84/0.30	28224

NOTE:

1. The rates mentioned are not including GST, which shall be charged extra.
2. This price list is subject to change without prior notice.
3. In accordance to the international practice adapted by the Bureau of Indian Standards the diameter of the conductor displayed above is nominal. The resistance determines by the size of the conductor.
4. WATTS & VOLT PVC Insulated Industrial multi core cables are available in 100 Mtrs coils packed in protective packaging.
5. WATTS & VOLT PVC Insulated cables are available in five colours : Red, Yellow, Blue, Black & Green.

