

Industrial Cables LP No. WILLCA Ultra Series (FR) MAY/ 2022 Dtd : 14-05-2022

PVC SINGLE CORE MULTI STRAND CABLES.

HSN CODE : 8544

WILLCA Ultra Series (FR) PVC INSULATED SINGLE CORE UNSHEATHED INDUSTRIAL MULTI-STRAND CABLE (FR) FLAME RETARDANT CONFORMING TO IS 694:2010 WITH HIGH QUALITY BARE CONDUCTOR SUITABLE FOR 1100 VOLTS

SIZE (Sq. mm.)	No. & SIZE OF WIRE IN MM	CURRENT (AMPS) BUNCHED & ENCLOSED IN CONDUIT OR TRUNKING	RATE PER 90 MTR COIL	STANDARD PACKING FOR 90 MTR	RATE PER 180 MTR COIL	STANDARD PACKING FOR 180 MTR	RATE PER 270 MTR COIL	RATE PER MTR
0.75	15/0.25	7	1260	20	2493	10	3744	14.00
1.0	20/0.25	11	1710	20	3393	10	5094	19.00
1.5	30/0.25	14	2601	16	5175	10	7767	28.90
2.5	50/0.25	19	4410	10	8784	5	13185	49.00
4.0	56/0.30	26	6210	6	12384			69.00
6.0	84/0.30	31	9207	4	18378			102.30

SIZE (Sq. mm.)	No. & SIZE OF WIRE IN MM	CURRENT (AMPS) BUNCHED & ENCLOSED IN CONDUIT OR TRUNKING	RATE PER 100 MTR COIL	STANDARD PACKING FOR 100 MTR	RATE PER 200 MTR COIL	STANDARD PACKING FOR 200 MTR	RATE PER MTR
10.0	142/0.30	51	17217	1		1	172.17
16.0	226/0.30	68	26316	1		1	263.16
25.0	354/0.30	86	38700	1		1	387.00
35.0	495/0.30	110	58600	1		1	586.00

WILLCA Ultra Series (FRLS) PVC INSULATED SINGLE CORE UNSHEATHED INDUSTRIAL (MULTI-STRAND CABLE : (FRLS) FLAME RETARDANT LOW SMOKE CONFORMING TO IS 694:2010. WITH HIGH QUALITY BARE CONDUCTOR SUITABLE FOR 1100 VOLTS.

SIZE (Sq. mm.)	No. & SIZE OF WIRE IN MM	CURRENT (AMPS) BUNCHED & ENCLOSED IN CONDUIT OR TRUNKING	RATE PER 90 MTR COIL	STANDARD PACKING FOR 90 MTR	RATE PER 180 MTR COIL	STANDARD PACKING FOR 180 MTR	RATE PER 270 MTR COIL	RATE PER MTR
0.75	10/0.30	7	1350	20	2376	10	4014	14.00
1.0	14/0.30	11	1764	20	3501	10	5256	19.00
1.5	22/0.30	14	2691	16	5355	10	8028	28.90
2.5	36/0.30	19	4590	10	9144	5	13725	49.00
4.0	56/0.30	26	6480	6	12924			69.00
6.0	84/0.30	31	9630	4	19224			102.30

Industrial Cables LP No. WILLCA Ultra Series (FR) MAY/ 2022 Dtd : 14-05-2022

WILLCA ULTRA SERIES FLEXIBLE PVC INSULATED MULTICORE UNSHEATHED INDUSTRIAL MULTISTRAND CABLE WITH BRIGHT ANNEALED ELECTROLYTIC BARE COPPER CONDUCTOR FOR VOLTAGE UPTO 1100V CONFORMING IS 694:2010**(Rate in Per 100 Mtrs.)**

SIZE (Sq. mm.)	COND. CONST. (No./DIA.MM)	2 CORE	3 CORE	4 CORE
0.75	10/0.30	3969	5400	6930
1.0	14/0.30	4950	6840	8730
1.5	22/0.30	7020	9360	12600
2.5	36/0.30	10800	15300	19800
4.0	56/0.30	16200	22500	30600
6.0	84/0.30	24300	33300	44100

3 CORE FLAT CABLES

SIZE (Sq. mm.)	COND. CONST. (No./DIA.MM)	RATE (Per 100 Mtrs.)
1.5	22/0.30	9450
2.5	36/0.30	15300
4.0	56/0.30	22500
6.0	84/0.30	32400

NOTE:

1. The rates mentioned are not including GST, which shall be charged extra.
2. This price list is subject to change without prior notice.
3. In accordance to the international practice adapted by the Bureau of Indian Standards the diameter of the conductor displayed above is nominal. The resistance determines by the size of the conductor.
4. WILLCA Ultra Series (FRLS) PVC Insulated Industrial Cables are available in 90, 180, and 270 Mtr coils packed in Master as Cartons mentioned above.
5. WILLCA Ultra Series (FRLS) PVC Insulated cables are available in five colours : Red, Yellow, Blue, Black & Green.
6. WILLCA WIRE & CABLES are marked with authentic coding of WILLCA FR and WILLCA ULTRA Series.

