



Industrial Cables LP No. WILLCA (FR) MAY/ 2022 Dtd : 14-05-2022

**PVC SINGLE CORE MULTI STRAND CABLES.**

**HSN CODE : 8544**

**WILLCA (FR) PVC INSULATED SINGLE CORE UNSHEATHED INDUSTRIAL (MULTI-STRAND) CABLE : WILLCA (FR) FLAME RETARDANT CONFORMING TO IS - 694:2010 WITH HIGH QUALITY BARE COPPER CONDUCTOR SUITABLE FOR 1100 VOLTS**

SIZE (Sq. mm.)	No. & SIZE OF WIRE IN MM	CURRENT (AMPS) BUNCHED & ENCLOSED IN CONDUIT OR TRUNKING	RATE PER 90 MTR COIL	STANDARD PACKING FOR 90 MTR	RATE PER 180 MTR COIL	STANDARD PACKING FOR 180 MTR	RATE PER 270 MTR COIL	RATE PER MTR
0.75	10/0.30	7	1035	20	2043	10	3060	11.50
1.0	14/0.30	11	1359	20	2700	10	4050	15.10
1.5	22/0.30	14	2088	16	4140	10	6210	23.20
2.5	36/0.30	19	3303	10	6588	5	9873	36.70
4.0	56/0.30	26	5022	6	10026			55.80
6.0	84/0.30	31	7326	4	14634			81.40
SIZE (Sq. mm.)	No. & SIZE OF WIRE IN MM	CURRENT (AMPS) BUNCHED & ENCLOSED IN CONDUIT OR TRUNKING	RATE PER 100 MTR COIL	STANDARD PACKING FOR 100 MTR	RATE PER 200 MTR COIL	STANDARD PACKING FOR 200 MTR		RATE PER MTR
10.0	142/0.30	51	14868	1		1		148.68
16.0	226/0.30	68	22302	1		1		223.02
25.0	354/0.30	86	32391	1		1		323.91
35.0	495/0.30	110	49914	1		1		499.14

**PVC MULTI CORE INDUSTRIAL MULTI STRAND CABLES**

**WILLCA FLEXIBLE PVC INSULATED MULTI CORE UNSHEATHED INDUSTRIAL MULTISTRAND CABLE WITH BRIGHT ANNEALED ELECTROLYTIC BARE COPPER CONDUCTOR FOR VOLTAGE UP TO 1100V CONFORMING TO IS 694:2010.**

**(Rate in Per 100 Mtrs.)**

SIZE (Sq. mm.)	COND. CONST. (No./DIA.MM)	2 CORE	3 CORE	4 CORE
0.75	10/0.30	3393	4248	5310
1.0	14/0.30	3717	4995	6147
1.5	22/0.30	5733	7110	10512
2.5	36/0.30	8496	11367	15292
4.0	56/0.30	13086	18054	24426
6.0	84/0.30	21240	28674	

**3 CORE FLAT CABLES**

SIZE (Sq. mm.)	COND. CONST. (No./DIA.MM)	RATE (Per 100 Mtrs.)
1.5	22/0.30	7758
2.5	36/0.30	12744
4.0	56/0.30	19116
6.0	84/0.30	28674

**NOTE :**

- The rates mentioned are not including GST, which shall be charged extra.
- This price list is subject to change without prior notice.
- In accordance to the international practice adapted by the Bureau of Indian Standards the diameter of the conductor displayed above is nominal. The resistance determines by the size of the conductor.
- WILLCA (FR) and WILLCA Ultra (FR) PVC Insulated Industrial Cables are available in 90, 180, and 270 Mtr coils packed in Master as Cartons mentioned above.
- WILLCA (FR) and WILLCA Ultra (FR) PVC Insulated cables are available in five colours : Red, Yellow, Blue, Black & Green.

